

Series: L-ALEV, B-ALEV, BH-ALEV

Pressed steel castors, medium duty brackets, with top plate fitting, wheel with elastic solid rubber tyre 'Blickle EasyRoll'

200 - 500 kg


RoHS



Blickle EasyRoll

Brackets: L/B/BH series - Made of pressed steel, swivel bracket with double ball bearing in the swivel head, strong central kingpin (wheel Ø 150-250 mm), swivel head seals. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.
Bracket overview: Page 65
Top plate drawings: Page 77
Wheel and swivel head 'stop-fix' brake: Page 80

Wheels: ALEV series - Tyres: Made of high-quality elastic solid rubber in smooth rolling quality 'Blickle EasyRoll', 65° shore A, black.
Wheel centre: Made of die-cast aluminium.
Bearing type: Two pressed-in ball bearings.
Detailed description: Page 171 and 45



5



Swivel castors	Fixed castors	Swivel castors with 'stop-fix' brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-ALEV 100K	B-ALEV 100K	L-ALEV 100K-FI	100	40	200	Ball bearing	125	100 x 85	80 x 60	9	36
L-ALEV 125K	B-ALEV 125K	L-ALEV 125K-FI	125	40	200	Ball bearing	150	100 x 85	80 x 60	9	40
L-ALEV 150K	B-ALEV 150K	L-ALEV 150K-FI	150	54	400	Ball bearing	190	140 x 110	105 x 75-80	11	60
L-ALEV 161K	B-ALEV 161K	L-ALEV 161K-FI	160	40	300	Ball bearing	195	140 x 110	105 x 75-80	11	60
L-ALEV 160K	B-ALEV 160K	L-ALEV 160K-FI	160	50	400	Ball bearing	195	140 x 110	105 x 75-80	11	60
L-ALEV 180K	B-ALEV 180K	L-ALEV 180K-FI	180	50	400	Ball bearing	215	140 x 110	105 x 75-80	11	60
L-ALEV 200K	B-ALEV 200K	L-ALEV 200K-FI	200	50	400	Ball bearing	235	140 x 110	105 x 75-80	11	65
L-ALEV 250K-3	BH-ALEV 250K	*	250	50	500	Ball bearing	295	140 x 110	105 x 75-80	11	77

* For the 'stop-top' brake version refer to 'Options'

Options



	With non-marking grey tyre	Electrically conductive version, black tyre	With 'stop-top' brake	With central braking system 'central-stop'	Directional lock (retro fit) 1 x 360° **	Directional lock (retro fit) 1 x 360° **	With synthetic (-FP) or steel (-FS) foot guard
Technical description page	38	36, 38	80	81	83	83	84
Product code suffix	-SG	-EL	-ST	-CS11	RI-03.01	RI-05.03	-FP / -FS
Available for	all sizes	Ø 100, 125, 160x40, 200, 250 mm	all sizes	wheel Ø 160+200 mm	wheel Ø 100-125 mm	wheel Ø 150-200 mm	upon request

** Only for swivel castors without brake